

MAB-DD Flanged

Flanged single cartridge housing for dangerous fluids

MAB-DD flanged housings are designed for the filtration of dangerous fluids that require the use of Stainless Steel materials with high chemical compatibility.

The MAB-DD series is equipped with a system for opening and closing designed in 304 stainless steel clamp with bolts/lock washers and hex brass nuts to avoid seizing.

Housings are available in two lengths and can install a wide range of 10" and 20" filter elements type SOE code 7 for liquids, gases and vapours filtration.



Caratteristiche principali

- Flanged in-line connections.
- Fit for wall fixing (N° 4 M6x6 threaded holes).
- Suitable for dangerous fluids of group no. 1 in accordance with CE 1272/2008.
- Conformity to accordance with PED (Pressure Equipment Directive) and with ATEX for equipment used in potentially explosive areas.

Construction materials

Housing:	316 Stainless Steel
Clamp closure:	304 Stainless Steel
Gaskets:	Viton (standard)

Surface finishing

Type L	Head: blasted & electropolished Bowl-welded : external polished / internal finely brushed & pickled
--------	--

Design and construction

In accordance to the European Directive PED 2014/68/UE and ATEX 2014/34/UE


Documentation

UE declaration of conformity PED / ATEX and user guide.

Modello	Connections In-Out A—B	Cartridges	Weight	Volume	Vent C	Drain D	Nominal dimension (mm) +- 5		
	EN 1092-1	Size	Kg	L	ISO 228	ISO 228	G	F	L
MAB-DD-P10-B7-DN15-L-FS	DN 15	SOE 2071	5,2	2,5	1/8"	1/4"	210	407	330
MAB-DD-P10-B7-DN25-L-FS	DN 25		6,2	2,5			210	401	
MAB-DD-P10-B7-DN40-L-FS	DN 40		8,5	2,5			234	395	
MAB-DD-P20-B7-DN15-L-FS	DN 15	SOE 2072	6,5	3,9			210	703	580
MAB-DD-P20-B7-DN25-L-FS	DN 25		7,5	3,9			210	695	
MAB-DD-P20-B7-DN40-L-FS	DN 40		9,7	4,0			234	688	

Code information

MAB-DD	P10	B7	DN25	L	FS					
Series	Cartridge Length		Cartridge Size		IN-OUT Connections		Surface Finising		O-ring material	
	P10	10"	B7	SOE code 7	DN15	1/2"	L	Standard	FS	FEP + Silicone
	P20	20			DN25	1"				
					DN40	1-1/2"				



Operating limits

Series	Fluid state	
	Gas max Temp. 150°C (302°F)	Liquid max Temp. 90°C (194°F)
MAB-DD-P10	0-16 barg	0-16 barg
MAB-DD-P20	0-12 barg	

In accordance with PED and ATEX Directives		
Fluid group	PED 2014/68/UE	ATEX 2014/34/UE
1 (dangerous)	Cat.I	II 2G Ex h IIC T160°C Gb II 2D Ex h IIIC T160°C Db

Accessories

Model	Description
KC-V-B-M8-XX-GF-PN40	Ball drain valve S.S. 304 1/4" MF gas

Bea Technologies Spa

Via Newton,4 -20016 Pero (MILANO) Italy
Tel.+(39) 02 339271 / Fax+(39) 02 3390713
mail:info@bea-italy.com
web:www.bea-italy.com

The data are informative and subject to change without notice. User is responsible for determining whether the product is fit for particular purpose and suitable for User's method of application.